

Information requirement for the electric local space heaters

Model identifier(s):G3FERRARI G60029				
Item	Symbol	Value	Unit	Item
Heat output				Type of heat input, for electric storage local space heaters only (select one)
Nominal heat output	P _{nom}	1.8-2.0	kW	manual heat charge control, with integrated thermostat
Minimum heat output (indicative)	P _{min}	0,9	kW	manual heat charge control with room and/or outdoor temperature feedback
Maximum continuous heat output	P _{max,c}	2,0	kW	electronic heat charge control with room and/or outdoor temperature feedback
				fan assisted heat output
Auxiliary electricity consumption				Type of heat output/room temperature control (select one)
At nominal heat output	e _{lmax}	0.000	kW	single stage heat output and no room temperature control
At minimum heat output	e _{lmin}	0.000	kW	Two or more manual stages, no room temperature control
In standby mode	e _{lSB}	0,0	kW	with mechanic thermostat room temperature control
				with electronic room temperature control
				electronic room temperature control plus day timer
				electronic room temperature control plus week timer
				Other control options (multiple selections possible)
				room temperature control, with presence detection
				room temperature control, with open window detection
				with distance control option
				with adaptive start control
				with working time limitation
				with black bulb sensor
Contact details	TREVIDEA SRL, Strada Consolare RN-RSM, 62 - 47924 - Rimini, Italy			

